

## GUIDE: Damp Mopping

### PURPOSE:

Damp mopping is a one step procedure that lengthens the time between refinishing the floor.

This maintenance method can be adapted to all resilient floors.

### PRODUCT TO USE:

Peerless Strobe Floor Maintainer.  
 Chemical is not hazardous see MSDS.

## PROCEDURE

### 1. PREPARE EQUIPMENT

Fill a bucket with a solution of STROBE.  
 Dilute 1 part cleaner to 80 parts warm water.  
 Transport the equipment to the work site.

### 2. PREPARE AREA

Set up the 'Wet Floor' signs. Move all obstacles and furniture.

### 3. DUST MOP

Dust mop floor. Follow the dust mopping procedure.

### 4. APPLY MOPPING SOLUTION

Place the mop in detergent solution, wring out until mop is damp.  
 Mop the area lengthwise along the skirting boards being careful not to allow the mop to come in contact with the wall side of the skirting boards. Then continue to mop using a "figure 8" motion on the balance of the area.

Rinse the mop frequently. Use the heel of the mop or hand pad to remove stubborn spots. Wipe off the skirting boards immediately if any water has been splashed on them.




### 5. CHANGE SOLUTION AND MOP FREQUENTLY

Use the correct dilution rate for detergent.  
 Always measure detergent solutions. The solution should be changed whenever it becomes dirty.

### 6. WHEN FLOOR HAS DRIED

Remove signs. Return all furniture and other items back to their respective places.



### 7. CLEAN MOP

Immediately clean up equipment at the conclusion of the procedure.  
 All buckets and wringers must be thoroughly washed, rinsed and allowed to dry.  
 All mops must be thoroughly washed and hung to dry, away from walls.  
 All other equipment is either washed or wiped down and stored in the proper location.

***Always ensure that all safety requirements are in place before commencing work and where required all personal safety equipment is available and worn by cleaning technicians.***