



R10 Additive

1 PRODUCT DESCRIPTION

Additive providing structure for increased slip-resistant safety.

- For **Dr. Schutz and Eukula 2-component water-based lacquers** in the top-coat
- Liquid compound for easy application.
- Slip resistance class P5 according to Australian standards and testing with PU Sealer
- Slip resistance class P4 according to Australian standard and testing with Strato Extreme
- Slip-resistance class R10 according to BGR 181 and DIN 51130.

2 AREAS OF APPLICATION

Can be combined with all Dr. Schutz Water-based sealers in the areas of application specified in their descriptions. **Dr. Schutz R10 Additive** is only used in the final lacquer coat.

Please pay attention to our technical instructions specifically for floors and buildings under www.dr-schutz.com.

3 APPLICATION

Shake up well! Mix Dr. Schutz R10 Additive in a ratio of 1:10 with the lacquer. Only when the desired quantity of lacquer has been mixed should the corresponding amount of cross-linker be added. Apply the top coat evenly with 50 ml/m².

Please note:

- Mixing into a lower coat of lacquer does not affect the sealing function, but does not contribute to slip resistance, either.
- If mixed lacquer is stored for a time, it must be carefully stirred up again.

4 CONSUMPTION

100 m²/500ml (5 g/m²) when applying lacquer of 50 ml/m² with additive at a ratio of 1:10.

7 STORAGE

Protect against frost. Store in a cool, dry place. Will keep for 24 months in unopened, original canister from the date of manufacture. Keep coating materials out of the reach of children.

8 TECHNICAL DATA

Contains substances: water, polyacrylat, silicic acids, waxes, additive. Contains a mixture of: 5-Chlor-2-methyl-2H-isothiazol-3-on and 2 Methyl-2H-isothiazol-3-on. Can cause allergic reactions.

pH 7,5

voc (g/l): <1 (ISO 11890)



R10 Additive

ADR/RID: not a dangerous good.

CLP: no labelling obligation.

Even when using low-pollution products the usual safety measures are to be observed. Keep out of the reach of children. Completely emptied canisters can be disposed of in domestic waste or at a recycling centre.

9 SPECIAL NOTES

10 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of Dr. Schutz finishes
- Safety data sheet.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage www.peerlessjal.com.au or on request from the address quoted below.

Dr. Schutz – We Care About Floors

Peerless JAL
Head Office
6-12 Raglan St, Preston
VIC, 3072

Ph: 1800 800 248
Fax: 03 9416 8516
Email: sales@peerlessjal.com.au
www.peerlessjal.com.au

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.