

# Domestic Vinyl Floor Program

SEALING AND CLEANING MAINTENANCE GUIDE WITH GEMINI SEALER FINISH

## **INITIAL CLEAN:**

After the flooring has been installed, completely clean the surface by sweeping and then thoroughly scrubbing with a liberal solution of PEERLESS VERSADET FLOOR CLEANER diluted 1 part to 30 parts water. Rinse with clean water and allow to dry.

## **ROUTINE MAINTENANCE:**

The frequency of maintenance will depend on the amount of foot traffic and surrounding environment.

Sweep regularly to remove all loose dust, dirt and foreign matter.

Spot mop general spillages as soon as they occur.

Wet clean the floor as required by damp mopping with a solution of PEERLESS VERSADET FLOOR CLEANER diluted 1 part to 60 parts water.

The provision of entrance matting will help prevent the entry of damaging and unsightly dirt and grit. Clean entrance matting regularly.

## **PERIODIC MAINTENANCE FOR HEAVILY TRAFFICKED HIGH WEAR AREAS:**

A polish can be applied in order to provide extra protection in the heavily trafficked areas and/or where a higher gloss finish is required.

Completely clean the surface as per 'INITIAL CLEAN'.

Old and discoloured polish or other residues should be removed by applying PEERLESS LAZER FLOOR STRIPPER diluted 1 part to 3 parts water. Using the diluted stripper solution thoroughly wet a small workable area and allow 5 minutes contact time before scrubbing. Pick up the scrubbed solution, rinse with clean water and allow to dry. Continue this method until the entire floor is totally stripped.

Apply 2 to 3 thin even coats of PEERLESS GEMINI SEALER FINISH using a clean mop or polish applicator, allowing 45 minutes between coats.

*INFORMATION contained in this program is to the best of our knowledge accurate and reliable; however no guarantee is given nor intended as conditions of handling and use is beyond our control. All products should be used in the standard manner and in accordance with label and product use directions. Observe all safety directions.*