

GUIDE: Spray Buffing

PURPOSE:

To maintain clean, shiny, attractive floors. This procedure removes a thin layer of dirty floor finish, replaces the same amount of finish, and burnishes the floor Product to Use Peerless Sprayglo Spray Buffing Compound. Chemical is not hazardous see MSDS. to a gloss.

PRODUCT TO USE:

Peerless Sprayglo Spray Buffing Compound.
Chemical is not hazardous see MSDS.

PROCEDURE

1. PREPARE EQUIPMENT

Set up 'Wet Floor' signs. Move all obstacles such as furniture.



2. DUST MOP FLOOR

Follow the dust mopping procedure.



3. DAMP MOP

Follow the damp mop procedure.

4. MACHINE BUFF FLOOR

Place the floor machine in position. Spray the floor with the spray buff solution and spread damp solution across the floor with the floor machine. Use a side to side motion, be careful to avoid bumping walls and furniture. Allow a slight overlapping on each pass. Buff until the haze is gone and the floor area has a shine. Do not allow floor pads to load up. Turn them over or change them frequently.



5. DUST MOP AGAIN

Pick up any dust resulting from buffing operation. Use a clean, oil free, dustmop.

6. WHEN FINISHED

Remove the caution signs. Return furniture and other items cleared from the area to their proper positions.



7. CLEAN UP

Immediately clean up equipment at the conclusion of the procedure. All floor pads must be thoroughly washed and allowed to dry. All other equipment must be either washed or wiped down and stored in the proper location.

Always ensure that all safety requirements are in place before commencing work and where required all personal safety equipment is available and worn by cleaning technicians.