

Friendly technology at work



hyseries

hyshield 

## Supermarket Maintenance Program - Basic

### DAILY MAINTENANCE

1. Dust mop floor.
2. Scrub floor with an auto scrubber and red pads, using **Peerless JAL Strobe Floor Maintainer** diluted 1:80.
3. Trail mop behind scrubber with clean rinse mop.
4. Buff floor with high-speed burnisher and with burnishing pad.
5. Dust mop floor.

### STRIPPING & FINISHING

1. Dust mop entire area.
2. Use **Peerless JAL Eraser Polish Remover** 1:6 in a mop and bucket.
3. Apply liberal amounts of solution uniformly on floor with mop. Let solution soak for five minutes. Keep area wet - do not allow solution to dry on floor.
4. Scrub with an auto scrubber or a slow speed buffer and black pads. Detail edges with edging tool. Use stronger stripper dilution when detailing edges.
5. Apply clean water with auto scrubber and pick up dirty solution with squeegee down and vacuum on. Rinse floor a second time with the addition of a small amount of vinegar in the rinse water - this acts as a neutralizer. Trail mop behind scrubber with a clean rinse mop.
6. Buff floor with high-speed burnisher and dust mop.
7. Apply 3 medium coats of **Peerless Jal Hy-Shield Hybrid Floor Finish**. A medium coat is approx 40m<sup>2</sup> per litre.
8. Should additional finish be required allow at least 24 hours drying time before applying one (1) more medium coat after the floor has been scrubbed clean, buffed and dust mopped.

### IN ONE OR TWO WEEKS

If desired, after one or two weeks when the finish has fully cured, a cut-back and re-coat may be executed. This will improve wear, increase time between stripping and finishing, and present the floor at its best.

### PERIODICALLY

As determined, at periodic intervals as the finish wears from foot traffic, execute a cut-back and re-coat to extend the life and presentation of the coatings.

hyshield 

bk



**PEERLESS JAL**  
Keeping it Clean since 1947

Friendly technology at work



hyseries

### CUTTING BACK & RE-COATING

1. Dust mop floor.
2. Lay scrub floor with black pads using **Peerless JAL Strobe Floor Maintainer** diluted 1:10 or **Activ SRA** diluted 1:20. Allow adequate solution contact time and scrub passes.
3. Trail mop behind scrubber with a clean rinse mop.
4. Buff floor with high-speed burnisher and dust mop.
5. Apply one (1) medium coat of **Peerless Hy-Shield Hybrid Floor Finish**. A medium coat is approx 40m<sup>2</sup> per litre.

### STOCKROOM

It is recommended the stockroom be scrubbed at least once weekly (wet mop clean inaccessible areas). This will reduce the volume of dirt entering the store. An auto scrubber fitted with a nylon brush is more effective in this area.

### CLEANING EQUIPMENT SCHEDULE

Equipment selection depends on the size of the trading floor, aisle widths and checkouts

Auto scrubber Suitable size is 43 – 50 – 65cm

High speed burnisher Polivac Stingray cord electric or Polivac 20 UHS gas propane buffer

Mops, buckets, scissor mops, sweep mops, etc

**Note: Do not apply finish to a dirty floor!**

### TECHNICAL ADVICE

Peerless JAL personnel can help to develop a program for each individual store and should be consulted as soon as possible.

*INFORMATION contained in this program is to the best of our knowledge accurate and reliable; however no guarantee is given nor intended as conditions of handling and use is beyond our control. All products should be used in the standard manner and in accordance with label and product use directions.*

bk hyshield 



**PEERLESS JAL**  
Keeping it Clean since 1947