

HYDROTHANE SPORTS FLOOR

Peerless JAL Pty Ltd

SCHEDULE FOR THE MAINTENANCE OF HYDROTHANE
TREATED TIMBER FLOORING

MAINTENANCE PROGRAM

To retain your timber floor in first class condition and protect your investment an adequate maintenance program should be established.

We recommend the following proven procedures.

ENTRANCE MATTING

- Dirt, grit and sand can be contained at the entrance if adequate matting is provided.
- An adequate mat program will eliminate the trafficking of damaging particles from scratching and prematurely wearing the surface.

CONTROL OF FOOTWEAR

- Street shoes should not be permitted on your timber floors if it is a sports floor. Establish a policy to allow only sports shoes on the playing surface and ensure the treads are free of damaging stones and grit.

REGULAR SWEEPING

- Fine dust and dirt will create a slip problem; establish a regular sweeping program to remove all dust.
- Synthetic sweeping mops, up to 2 metres in length provide a fast and effective method of sweeping large open areas.
- For smaller obstructed areas smaller sweep mops are available.
- Dust control solutions are not required when using synthetic fibre sweeping mops.
- The use of Dust Control Emulsions is not recommended under any circumstances as they can cause hazardous slip problems through the deposition of oil onto the playing surface.

WET CLEANING

- A regular wet cleaning program will enhance your floor and keep it clean, dirt free and safer.
- The use of harsh detergents is not recommended nor is it necessary. Peerless JAL GYMCLEAN has been specifically formulated for the wet cleaning of timber floors treated with Peerless JAL HYDROTHANE 'SPORT'. The most efficient and adequate method of wet cleaning a

large area is with an Automatic Scrubber¹ that lays down cleaning solution, scrubs the floor and wet vacuums the dirty solution leaving a clean, dry floor For small, congested areas wet cleaning can be effected by a simple bucket and mop application – follow use directions on the Peerless JAL GYMCLEAN label.

- Do not start your wet cleaning program for 7 days after the application of Peerless JAL HYDROTHANE ‘SPORT’, when it has reached its maximum detergency resistance.

Note: The use of Peerless JAL TIMBER PRECLEAN is not recommended as a maintenance cleaner. It is only designed as a preclean for use prior to retreatment with Peerless JAL HYDROTHANE ‘SPORT’.

BUFFING

- A pleasing gloss level can be maintained on your timber floor by the regular use of a polishing machine.
- This is used after the wet cleaning procedure.
- Burnishing also enhances the general appearance of the floor by minimizing scuff and rubber burns on the floor surface.

At periodic intervals your timber floor will require treatment by way of additional coats of Peerless JAL HYDROTHANE ‘SPORT’. We recommend that you thoroughly inspect your floor at regular intervals and schedule a retreatment of Peerless JAL HYDROTHANE ‘SPORT’, prior to major restoration or full sanding being required. This will provide a lifetime of use from your timber floor.

¹ A range of Auto Scrubbers, High Speed Buffing and Burnishing equipment is available from your local Peerless JAL Sales Office and our consultants can advise on the most suitable type for your individual application.

CONTACT DETAILS

HEAD OFFICE VICTORIA

10-12 Raglan Street PRESTON 3072

PH

03 9416 6700

FAX

03 9416 8516

BRANCHES THROUGHOUT AUSTRALIA

*Melbourne, Ballarat, Sydney, Brisbane, Adelaide,
Perth, Kalgoorle, Darwin, Hobart*

1800 800 248

EMAIL: sales@peerlessjal.com.au

WEBSITE: www.peerlessjal.com.au