

ELEGANCE

UHS Sealer Finish

PRODUCT INFORMATION SHEET

DESCRIPTION:

ELEGANCE Floor Sealer Finish utilizes the advances in acrylic coating technology to produce a floor finish that provides exceptional wear resistance with a pleasing wet look appearance.

ELEGANCE provides safety underfoot, good black heel mark resistance, exhibits instant burnish response and is designed for large high traffic areas requiring a consistent high gloss appearance, the mode of maintenance is auto scrubbing and Ultra High Speed burnishing.

ELEGANCE also contains a unique preservative system that aids in the prevention of bacterial growth, when floors are properly maintained.

ELEGANCE is deemed to comply AS/NZS 4586 – 1999 Slip Resistance of Pedestrian Surfaces for dry slip.

FEATURES AND BENEFITS:

- Exceptional wear resistance with a wet look appearance
- Safe underfoot
- Designed for heavy traffic areas
- Contains unique preservative system to aid in the prevention of bacterial growth.

TECHNICAL INFORMATION:

Appearance	Opaque white liquid
Odour	Acrylic polymer
pH	8.5 – 9.5
Specific Gravity	1.022 ± 0.005
Percentage Volatiles	73.0 – 72.5%
Coverage	50 – 80 m ² /litre (Typical)

USE:

The floor surface must be thoroughly cleaned and dry. Old or discoloured polish should be stripped from the floor with **ERAZER** or **LAZER SUPER** Floor Stripper. Buffing or burnishing the flooring prior to application of **ELEGANCE** will further enhance its final appearance.

Note: When stripping waxes and polishes from timber floors, **ALL PURPOSE STRIPPING EMULSION** must be used. ERAZER AND LAZER SUPER are unsatisfactory on timber floors as in some instances it may affect the seal.

Apply **ELEGANCE** undiluted, direct to the floor using your preferred application method.

Thin coats are preferable to minimize dry times and provide quicker cure time. Allow each coat to dry before application of further coats.

To produce optimum results, one coat of **AQUASEAL** Semi Permanent Sealer is applied to fill and prepare the floor surface. After this procedure apply 3 – 4 coats of **ELEGANCE**.

To retain a clean gloss floor, provide a daily maintenance system incorporating Peerless Pro Products.

SAFETY: This material is not classified as hazardous according to criteria of Safe Work Australia

Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.