



## euku refresher

### 1 PRODUCT DESCRIPTION

Refresher for oxidative impregnated-oiled floors. Follow-up impregnation based on natural oils and waxes for the care treatment of floors in private residences and public buildings.

- Preserves the natural surface,
- Optimizes oiled floors hard-wearing capability,
- For spot-cleaning and touching up,
- Highly water repellent.

### 2 AREAS OF APPLICATION

Deeply effective follow-up impregnation of tired, dry wood and parquet floors in the framework of regular care. Due to its liquid consistency also suitable for impregnating furniture, wood panels, etc.

### 3 APPLICATION

Clean the floor thoroughly before treatment with a slightly damp mop. Apply **euku refresher** onto the floor with a cloth. After allowing it to soak in for 30 minutes polish out the remaining excess. Do not allow any moist oil to remain on the surface.

Please note:

- Optimal application is with the T-Wiper and cloth-strip.
- For polishing out on large areas we recommend using a monodisc-machine.

### 4 CONSUMPTION

Depending on the absorbency of the subsurface. Guideline: approx. 20-30 m<sup>2</sup>/L (30-50 ml/m<sup>2</sup>).

Higher consumption is possible in the case of coarse sanding, wider joints and highly absorbent wood, although subsequent applications will use considerably less.

### 5 DRYING TIME

Can be walked on carefully, or worked on again, after about 24 hours (at 23 °C, 50% relative humidity and air movement). The area should not be mopped wet in the first 7 days afterwards. After 10 days at the earliest carpets can be laid on the floor.

Low temperatures, increased humidity, poor ventilation and drying inhibiting wood ingredients can extend the drying time substantially.

### 6 CLEANING / CARE

Please note that the surface image of an oil-impregnated floor is only finalized after use, cleaning and care. After

## euku refresher



complete hardening, use **Peerless JAL Versadet** for cleaning and care and **euku refresher** for subsequent oil care. Please observe eukula care instructions for oil impregnated floors.

### 7 STORAGE

24 months in an unopened original canister. Remove any skin which may have formed before use. Store in a cool, dry place. Keep out of the reach of children.

### 8 TECHNICAL DATA

Contains substances: natural oils and waxes, modified vegetable oils, aliphatic solvents, drying agents free of lead and cobalt.

voc (g/l) 492 / GISCODE: Ö60+ / 2004/42/IIA(f)(700)700

ADR/RID: not a dangerous good as defined by transport regulations.

CLP: The product is not classified according to the CLP regulation.

Even when using low-pollution products, the usual safety measures are to be observed. Keep out of the reach of children. Completely emptied canisters can be disposed of in domestic waste.

### 8 SPECIAL NOTES

- Warning! Danger of self-combustion of oil-soaked working materials, such as cloths, fleeces, sanding dust, etc. These should be enclosed in an air-tight metal container, or soaked with water and disposed of in a fire-safe way. The oil itself is not self-combusting.
- Oiled surfaces smell. The smell diminishes with increasing drying in the course of days. In the initial time after an oil treatment ventilate the rooms well.

### 9 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes
- Safety data sheet.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage [www.peerlessjal.com.au](http://www.peerlessjal.com.au) or on request from the address quoted below.

## euku refresher



### eukula – We Care About Wood Floors

Peerless JAL  
Head Office  
6-12 Raglan St, Preston  
VIC, 3072

Ph: 1800 800 248  
Fax: 03 9416 8516  
Email: [sales@peerlessjal.com.au](mailto:sales@peerlessjal.com.au)  
[www.peerlessjal.com.au](http://www.peerlessjal.com.au)

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.