



eukula G200A

1 PRODUCT DESCRIPTION

Sealer for wood, parquet and cork floors. Alcohol based mild in odor. Gives wood a warm color. Blocking primer against interaction with topcoats.

- Attractive wood warming appearance
- Tannin and oil blocking primer
- Quick drying,
- Reduced grain raise,
- Reduces edge bonding.
- Can be used with all eukula and strato sealers.

2 AREAS OF APPLICATION

Primer for wood and parquet floors before top coating with all strato lacquers.

3 APPLICATION

Apply rich and evenly with the Aquatop-Roller.

- The professionally sanded and grouted subsurface must be in a clean, dry condition, free of oil, wax and dust.
- Room and material temperature must not be allowed to fall below +15°C during application and drying time.
- The rules of the professional trade are to be observed.

4 CONSUMPTION

Approx. 8-10 m²/l (100-120 ml/m²). In the case of highly absorbing wood increased consumption is possible.

5 DRYING TIME

Can be carefully walked on, or worked on again with UA- and PU-lacquers, after about 60-90 minutes (at 20 °C and 50% relative humidity, ventilation).

Low temperatures, increased humidity, poor ventilation and drying inhibiting wood ingredients can extend the drying time substantially.

7 STORAGE

Store in a cool dry place. Can be stored for 24 months from date of manufacture in unopened original canister. Keep coating materials out of the reach of children.



eukula G200A

8 TECHNICAL DATA

Contains substances: alcohols, synthetic resins.

voc (g/l) 747 (ISO11890) / GISCODE: G1 / 2004/42/IIA(h)(750)750.

ADR/RID: UN1263, PAINT RELATED MATERIAL, 3, III.

CLP: GHS02, GHS07, Danger. H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapours. P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

8 SPECIAL NOTES

- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of a different batch, mix this in a separate container before using.
- With strongly enhanced humidity whitish drying due to condensing water is possible. Repeat application with better conditions.

9 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes
- Safety data sheet.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage www.peerlessjal.com.au or on request from the address quoted below.

eukula G200A



eukula – We Care About Wood Floors

Peerless JAL
Head Office
6-12 Raglan St, Preston
VIC, 3072

Ph: 1800 800 248
Fax: 03 9416 8516
Email: sales@peerlessjal.com.au
www.peerlessjal.com.au

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.