

QB DEGREASER

Solvent Based Industrial Degreaser

PRODUCT INFORMATION SHEET

DESCRIPTION:

QB DEGREASER is a ready to use solvent based industrial degreaser that exhibits superior degreasing power with quick break properties.

QB DEGREASER Will quickly dissolve a wide range of organic soils due to its unique blend of solvents. Waste generated from degreasing operations may be disposed of as oily waste due to the high boiling point of these solvents used.

QB DEGREASER has a scientific blend of surfactants that are designed to emulsify soils then permit rapid separation of the emulsion, when static conditions occur. This property allows maximum efficiency of any affluent management system employed, and thus minimises impact on biodegradation processes.

QB DEGREASER Is an excellent solvent formulation for use in parts washing machines due to its solvent power, low odour, and ability to separate insoluble soils rapidly from the bulk solvent phase. Baths pumps etc will last much longer if insolubles are able to be removed from the holding tank.

FEATURES AND BENEFITS:

- Powerful solvent action for removal of a wide range of soils.
- Quick break formulation for more efficient effluent management
- High boiling solvents to permit disposal as oily waste
- Excellent insoluble soil rejection for longer bath life
- Ready to use formulation for maximum convenience

TECHNICAL INFORMATION:

Appearance	Clear brown liquid
Odour	Mild Solvent - Flammable
pH	2.0-3.0
Specific Gravity	0.826
Percentage Volatiles	95%
Solubility in Water	Emulsifies

USE:

QB DEGREASER should be used as supplied and may be applied by spray, swab dip or brush techniques to remove oil and grease from most surfaces. Allow a short time for solvent to penetrate soil, then remove by pressure washing or draining. Emulsions produced from rinsing operations should be allowed to stand in a static environment for approximately 10 minutes to permit all organic materials to separate from the water phase. The upper organic (solvent) phase may then be skimmed and disposed of as oily waste. For parts washing machines, simply fill tank with **QB DEGREASER** and use as normal. To remove insoluble material from tank, allow to stand for 1 hr, then decant top solvent layer, remove bottom sludge from tank, then replace solvent layer.

SAFETY: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective clothing, gloves, eye/face protection and suitable respirator.