

strato frost prime 202



1 PRODUCT DESCRIPTION

Waterbased Sealer for wood, parquet and cork floors with brightening pigmentation, low emission and almost odorless.

- Cool coloration due to whitish brightening effect.
- Roller primer for wood floors of light wood.
- Quick drying, reduced grain raise.
- Reduces edge bonding
- Suitable for under-floor heated floors.
- Can be used under all strato lacquers.
- Giscod W2+, low emissions and low odour.

2 AREAS OF APPLICATION

For priming light wood and parquet floors (*) before the final finish with strato lacquers. Especially recommended for light types of wood (Blackbutt, Tas Oak etc.) to preserve their light tone. We recommend testing before use on dark types of wood.

3 APPLICATION

Shake up **strato frost prime 202** well, apply evenly and generously with the Aquatop-Roller onto the finely sanded floor. If a stronger white tone is desired, a second coat is possible, whereby an interim sanding with 180 mesh is recommended, do not sand right down. Finally apply two coats of strato lacquer.

Please note:

- The subsurface must be professionally sanded and grouted before application and must be clean and dry, free of oil, wax and dust. We recommend fine sanding with 120 grain.
- Tip: wet mopping of the raw wood with a short drying interval until it appears dry, reduces the absorbency of the wood when the water-based lacquer is applied and makes the coloration more uniform.
- Wood which has largely been dried from below (e.g. in renovation sanding on an under-heated floor) should be wet-mopped before lacquering, in order to avoid colour marks in the process.
- Room and material temperature must not fall below +15°C during application and drying time.

4 CONSUMPTION

Approx. 7-8 m²/l (120-150 ml/m²) per coat.

For best results and an even surface image, work in thick layers. In the case of highly absorbing wood increased consumption is possible.

5 DRYING TIME

Can be walked on carefully and worked on again after approx. 3 hours (at 20 °C, 50% relative humidity and air movement).

strato frost prime 202



In order to avoid excess soaking of the wood, only one rolled coat of water-based lacquer is recommended per day. Low temperatures, increased humidity and poor ventilation can prolong drying time substantially.

Tip: in order to remove the water, accelerate drying and reduce moisture in the wood, we recommend using a ventilator/ blower.

7 STORAGE

Protect from frost. Store in a cool dry place. Can be stored for 12 months from date of manufacture in unopened original canister. Keep coating materials out of the reach of children.

If stored in changing temperatures and in opened canisters, dry parts can form. Filter these out with a sieve before using.

8 TECHNICAL DATA

Contains substances: water, polyacrylates, polyurethanes, silicic acid, waxes, glycol ethers, additives. Contains 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

voc (g/l) 47 (ISO11890) / GISCODE: W2+ / 2004/42/IIA(i)(140)140.

ADR/RID: not a dangerous good as defined by transport regulations.

CLP: The product is not classified according to the CLP regulation.

Even when using low pollution products, the usual safety measures are to be observed. Keep out of the reach of children. Completely emptied canisters can be disposed of in domestic waste.

9 SPECIAL NOTES

- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of a different batch, mix this in a separate container before using.
- Clean working tools with water. We recommend that you leave the well-washed roller fully covered in water, in order to avoid it drying out. However, when the roller is used anew for application, no water must be allowed to mix with the lacquer.
- It is possible to apply the product to all types of wood. In the case of exotic woods, their characteristic appearance may be affected by the specific properties of the wood. We recommend testing beforehand.

10 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes
- Safety data sheet available on request.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage www.peerlessjal.com.au or on request from the address quoted below.

strato frost prime 202



eukula – We Care About Wood Floors

Peerless JAL
Head Office
6-12 Raglan St, Preston
VIC, 3072

Ph: 1800 800 248
Fax: 03 9416 8516
Email: sales@peerlessjal.com.au
www.peerlessjal.com.au

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.