

euku premium antislip R10 add

1 PRODUCT DESCRIPTION

Optional system component for adding to **euku premium hardwax oil +**. Additive providing structure for increased slip resistant safety.

- Mixture ratio 1:10
- Liquid compound for easy handling.
- Effective in result.
- Slip resistance class R10 according to BGR 181 and DIN 51130.

2 AREAS OF APPLICATION

To be applied in the final coating for the basic treatment of sanded wood and parquet floors, as well as cork floors and particle board (OSB board) with **euku premium hardwax oil +**.

3 APPLICATION

Add to the euku hardwax oil + system in a ratio of 1:10 and mix together. Work with the mixture as described in the system.

4 CONSUMPTION

approx. 200-250 SQM/L for single application in the top coat.

5 DRYING TIME

As described for the euku hardwax oil + system

6 CARE & MAINTENANCE

As described for the euku hardwax oil + system

7 STORAGE

24 months in unopened, original canister. Store in a cool, dry place. Keep out of the reach of children.

8 TECHNICAL DATA

Contains substances: aliphatic hydrocarbons, silicic acids, filler, additives.

ADR: Not a dangerous good as defined by transport regulations.

CLP: EUH066 repeated contact may cause skin dryness or cracking.

euku premium antislip R10 add

9 SPECIAL NOTES

10 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes
- Safety data sheet available on request.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage www.peerlessjal.com.au or on request from the address quoted below.

eukula – We Care About Wood Floors

Peerless JAL
Head Office
6-12 Raglan St, Preston
VIC, 3072

Ph: 1800 800 248
Fax: 03 9416 8516
Email: sales@peerlessjal.com.au
www.peerlessjal.com.au

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.